



SPX UNIVERSAL COOLANT/ANTIFREEZE 50/50

CONVENTIONAL ETHYLENE GLYCOL BASED GREEN UNIVERSAL
COOLANT/ANTIFREEZE

SPX Universal Coolant/Antifreeze 50/50 is a conventional (green) ethylene glycol based fluid specially formulated with premium additives for optimal performance in cooling system rust and corrosion protection. SPX Universal Coolant/Antifreeze 50/50 is designed for use in all makes and all models of automobiles and light duty trucks.¹

Features & Benefits

- Protects against rust and corrosion of all cooling system metals, including aluminum
 - Compatible with all major American brands of conventional coolants
 - Low silicate formulation
 - High-quality defoamer system, non-harmful to hoses, plastics, or gaskets
 - Protects against winter freeze up and minimizes chances of summer boil over
 - Manages inventory costs by using in mixed fleet applications where both cars and light trucks are present from various manufacturers
-

Applications

- All makes and all models of automotive and light duty trucks¹
 - Ideal for conventional antifreeze applications
 - General service applications where cooling system warranty maintenance is not required
-

¹Check with your OEM for specific application requirements.

Web: www.pilotthomas.com

Email: ptl.orders@pilotthomas.com

Tel: 844.785.8326



SPX UNIVERSAL COOLANT/ANTIFREEZE 50/50

TYPICAL PROPERTIES

| | |
|--|-------------|
| Appearance | Green |
| Specific Gravity @ 60°F, ASTM D1122 | 1.070-1.080 |
| Freezing Point, °C, ASTM D1177 | -37 max |
| Boiling Point, °C, ASTM D1177 | 130 min |
| pH, ASTM D1287 | 10.0-11.0 |
| Reserve alkalinity, ASTM D1121 | 5.0-7.0 |
| Ash, wt%, ASTM D1119 | 2.5 max |
| Silicon, ppm | <125 |
| Chloride, ppm | <25 |

BOIL OVER & FREEZE PROTECTION

| | |
|--|---------|
| Boiling Protection, °F/°C (using a 15lb pressure cap) 50% 1:1 (1 part antifreeze/1 part water) | 265/129 |
|--|---------|

| | |
|--|---------|
| Freezing Protection, °F/°C 50% 1:1 (1 part antifreeze/1 part water) | -34/-37 |
|--|---------|

Note:

- Product concentrates should be agitated before use
- Always dispose of used coolant in accordance with local, state, and federal guidelines

Minor variations in typical properties data are to be expected in normal manufacturing.